

BESL3 SERIES 120VAC DIRECT PLUG-IN SCREWDRIVERS

1.33–43.4 in-lbs (0.15–4.9 Nm)

- Clean, brushless motor technology
- Dependable, long lifespan
- Outperforms brush-type drivers
- Plugs directly into 115VAC receptacle
- Input 110–120VAC, 50/60Hz, 48W
- Integral 3m power cord w/ US plug
- Lever or push start models available
- Right angle versions available



Tool Includes



TORQUE LOCK SLEEVE

SUSPENSION BAIL

1/4" HEX BITS:
BESL300–301: PH#1, #2
BESL302: PH#2 (x2)

Model Number	Start Type	Torque Range		Speed (rpm)	Length in / mm	Diameter in / mm	Weight lbs / g
		in-lbs	Nm				
BESL300	Lever	1.33–10.44	0.15–1.18	1200	9.6 / 245	1.4 / 36	1.0 / 470
BESL300P	Push	1.77–10.44	0.2–1.18	1200			
BESL300F	Lever	1.33–10.44	0.15–1.18	2000			
BESL300PF	Push	1.77–10.44	0.2–1.18	2000			
BESL301	Lever	3.47–19.12	0.39–2.16	1200			
BESL301P	Push	3.47–19.12	0.39–2.16	1200			
BESL301F	Lever	2.57–14.78	0.29–1.67	2000			
BESL301PF	Push	2.57–14.78	0.29–1.67	2000			
BESL302LT	Lever	4.34–21.7	0.49–2.45	1000	11.0 / 280	1.5 / 38	1.6 / 740
BESL302PLT	Push	4.34–21.7	0.49–2.45	1000			
BESL302FLT	Lever	4.34–21.7	0.49–2.45	2000			
BESL302PFLT	Push	4.34–21.7	0.49–2.45	2000			
BESL302	Lever	17.4–43.4	1.96–4.9	1000			
BESL302P	Push	17.4–43.4	1.96–4.9	1000			

Right Angle Model Number	Start Type	Torque Range		Speed (rpm)	Length in / mm	Diameter in / mm	Weight lbs / g
		in-lbs	Nm				
BESL300-RA	Lever	1.06–8.35	0.12–0.94	1200	11.4 / 290	1.4 / 36	1.6 / 720
BESL300F-RA		1.06–8.35	0.12–0.94	2000			
BESL301-RA		2.77–15.30	0.31–1.73	1200			
BESL301F-RA		2.06–11.82	0.23–1.34	2000	13.3 / 337	1.5 / 38	2.2 / 990
BESL302LT-RA		3.0–15.2	0.34–1.71	1000			
BESL302FLT-RA		3.0–15.2	0.34–1.71	2000			
BESL302-RA		12.2–30.4	1.37–3.43	1000			



7370 Commercial Circle, Fort Pierce, FL 34951

772.465.4302

www.deltaregis.com

sales@deltaregis.com