

Talk to one of our application specialists TODAY!



Quality industrial products & excellent support for over 20 years!

[Electric Screwdrivers](#)

[Cordless Screwdrivers](#)

[Manual Screwdrivers](#)

[Screw Presenters](#)

[Torque Measurement](#)

[Tool Supports & Balancers](#)

[Smart Systems](#)

[Accessories](#)



**Complete System \$4900**

**DR-XTC1**  
Transducerized Torque Control System

- Real-time data collection
- Intuitive & User friendly software
- Endless rundown configurations
- Dynamic job selection

Software included  
No Additional Cost!

**deltaOnpoint**  
DATA CONTROL SOFTWARE by Delta Regis

# DR-XTC1

Transducerized Torque Control System  
0.05 ~ 18 Nm (0.4 ~ 159 in-lbs)

Take a look!

Want to test it out on your application before you buy!?

Take advantage of our free Test Drive program today!

Email us to start your Test Drive



The DR-XTC1 allows you to be in full control of your entire fastening process.

Easily setup multiple tightening parameters like speed, thread, direction & torque through the controller directly or via PC with deltaOnpoint software installed.

Create multiple jobs for different assembly stages and quickly switch between desired job dynamically.

Tightening data can viewed instantly in the deltaOnpoint software and can also be stored locally on an SD card to avoid data loss due to untimely internet connectivity issues.



# deltaOnpoint

DATA CONTROL SOFTWARE by Delta Regis

**Software Included at NO ADDITIONAL COST!**

With purchase of DR-XTC1 and appropriate ESL-XTE Series Transducerized Screwdriver

# Multiple screwdriver models available!

Choose the best transducerized DC driver to suit your application...



**ESL-XTE3LT**  
0.05~3 Nm (0.4~26 in-lbs)  
Max Speed: 980 RPM



**ESL-XTE3**  
0.6~3 Nm (5~26 in-lbs)  
Max Speed: 1100 RPM



**ESL-XTE3F**  
0.6~3 Nm (5~26 in-lbs)  
Max Speed: 1600 RPM



**ESL-XTE5**  
1.0~5.0 Nm (9~44 in-lbs)  
Max Speed: 1100 RPM



**ESL-XTE7**  
1.4~7.0 Nm (12~62 in-lbs)  
Max Speed: 660 RPM



**ESL-XTE12**  
2.4~12 Nm (21~106 in-lbs)  
Max Speed: 750 RPM



**ESL-XTE18**  
3.6~18 Nm (31~159 in-lbs)  
Max Speed: 450 RPM



- Real-time rundown information
- Intuitive visual feedback
- Quickly program and adjust desired parameters
- Data collection & monitoring capabilities
- Snapshot view shows you all rundown parameters at a glance

Contact us today for more information!



[www.deltaregis.com](http://www.deltaregis.com)

7370 Commercial Circle  
Fort Pierce, FL 34951  
772.465.4302



Contact Us