

Talk to one of our application specialists today!!



Quality industrial products & excellent support for over 25 years!

- [Electric Screwdrivers](#)
- [Cordless Screwdrivers](#)
- [Manual Screwdrivers](#)
- [Screw Presenters](#)
- [Torque Measurement](#)
- [Tool Supports & Balancers](#)
- [Smart Systems](#)
- [Accessories](#)

## ESB4-SXI Series Programmable Impact Drivers

5 ~ 200 Nm (3.7 ~ 147.5 ft-lbs)

- Multiple tightening parameters for accurate torque shut-off
- Powerful Li-Ion battery for high duty cycle applications
- Clean & maintenance free brushless motor
- Cross-thread & strip-out detection



**NEW**  
ESB4-SXI-200  
200Nm (147.5 ft-lbs)  
Now Available!

### Expect more from your impact tools

The ESB4-SXI Series of Production Assembly Impact Drivers with Torque Control gives you the ability to take control of your impact applications.

- High speed helps increase user efficiency
- Screw counter helps operator know exactly where they are in the fastening process
- Run in Reverse (Counter-clockwise operation) function
- Ignore friction function helps to further increase repeatability when working with multiple joint types and material
- Easily programmable with DR-IRC1 IR Remote Control
- Includes settings lock out function to help avoid tampering
- Customize up to 5 separate application programs, which are a combination of impact force, impact blows and screw rotation parameters which can be used individually or in sequence
- Internal voltage monitoring ensures fastening consistency by disabling the tool if battery levels are less than optimal
- OK & NG indicator provides instant feedback to the user helping to detect cross-threading and stripping

Specifications				
Model	ESB4-SXI-50	ESB4-SXI-70	ESB4-SXI-100	ESB4-SXI-200
Input Voltage	14.4V			
Speed (RPM)	0~1900	0~2600	0~2000	0~1700
BPM	0~2500	0~3400	0~2600	0~2100
Torque Range	5~50 Nm (3.7~36.9 ftlb)	20~70 Nm (14.7~51.6 ftlb)	20~100 Nm (14.7~73.7 ftlb)	25~200 Nm (18.4~147.5 ftlb)
Recommended Fastener Size (Class 12.9)	M6 / M8 / M10 / M12	M8 / M10 / M12 / M14	M10 / M12 / M14 / M16	M12 / M14 / M16 / M20
Torque Range Capability (Based on fastener size)	M6 - 3~20Nm (2.2~14.7 ftlb)	M8 - 8~30Nm (5.9~22.1 ftlb)	M10 - 8~40Nm (5.9~29.5 ftlb)	M12 - 15~110Nm (11.0~81.1 ftlb)
	M8 - 3~20Nm (2.2~14.7 ftlb)	M10 - 8~40Nm (5.9~29.5 ftlb)	M12 - 20~70Nm (14.7~51.6 ftlb)	M14 - 25~120Nm (18.4~88.5 ftlb)
	M10 - 5~30Nm (3.7~22.1 ftlb)	M12 - 20~60Nm (14.7~44.2 ftlb)	M14 - 20~90Nm (14.7~66.3 ftlb)	M16 - 25~140Nm (18.4~103.2 ftlb)
	M12 - 12~50Nm (8.8~36.9 ftlb)	M14 - 25~70Nm (18.4~51.6 ftlb)	M16 - 28~100Nm (20.6~73.7 ftlb)	M20 - 25~200Nm (18.4~147.5 ftlb)
Drive Type	1/4" Hex		3/8" Square	1/2" Square
	3/8" Square *Add suffix "-SQ**"		**Available in 1/2" Square Special Order**	
Weight (Less Battery)	0.98 kg (2.1 lbs)	1.0 kg (2.2 lbs)		1.5 kg (3.3 lbs)
Dimensions (Less Battery)	174x202mm (6.8x7.8")			219x220mm (8.6x8.7")
Battery	SKC-LB1425			
Charger	ESB-CHG70			
Optional Accessories	DR-IRC1			

We are so confident with the performance of our entire line of tools & accessories that if you find a better price on any

comparable product we will beat it!

Contact us for Price Match!



### ESB4-SXI-200

25 ~ 200 Nm (18.4 ~ 147.5 ft-lbs)

Take A Look!



### ESB4-SXI-50

5 ~ 50 Nm (3.7 ~ 36.9 ft-lbs)

Take A Look!



### ESB4-SXI-70

20 ~ 70 Nm (14.7 ~ 51.6 ft-lbs)

Take A Look!



### ESB4-SXI-100

20 ~ 100 Nm (14.7 ~ 73.7 ft-lbs)

Take A Look!

## Get all the accessories you need & SAVE 5%!

The Get Started Kit comes with:

- 2 Batteries (SKC-LB1425)
- 1 Charger (ESB-CHG70)
- 1 Remote (DR-IRC1)

More info...





Contact Us